



CARBON FOOTPRINT OF PRODUCTS

GREENHOUSE GAS EMISSIONS REPORT BETWEEN 2022 AND 2023

Table of contents

List	t of ak	breviations	3
Int	roduc	tion	5
1.	Orga	nizational boundaries	6
2	Oper	rational boundaries	7
3	Repo	orting period	8
4.	Meth	nodology	9
	4.1.	Fuels	9
	4.2.	Process gases	9
	4.3.	Purchased electricity	10
	4.4.	Cat. 1 Purchased raw materials and services	11
	4.5.	Cat. 3. Energy and fuel-related emissions not included in Scope 1 and 2	12
	4.6.	Cat. 4. Upstream – transport and distribution	13
	4.7.	Cat. 5. Waste generated from activities	14
	4.8.	Cat. 6 Business travel	14
	4.9.	Cat. 9 Downstream – transport and distribution	15
	4.10.	Cat. 12. Dealing with sold products after their end of life	15
	4.11.	Biogenic emissions – outside the scopes	15
5.	Emis	sion indicators and conversion rates	16
6.	Resu	Its and commentary	17
7.	Resu	Its of CO ₂ emissions calculations for 2022-2023	18
	7.1.	Carbon footprint – emissions by scope with biogenic emissions	18
	7.2.	Carbon footprint by emission category – market-based method	20
	7.3.	Carbon footprint – location-based method	22
	7.4.	Carbon footprint – market-based method	24
	7,5.	Biogenic emissions – outside the scopes	26
8.	Prod	uct carbon footprint – overview	27
	8.1.	Product nomenclature	27
	8.2.	Unit of analysis and reference flow	28
	8.3.	Range of calculations for products	28
	8.4.	Allocation	29
	8.5.	Data and data sources	29
	8.6.	Emission indicators and conversion rates	30
9.	Resu	Its and commentary	31
	9.1.	Carton	33
	9.2.	Flyer	31
	9.3.	Label	31
10.	Redu	uction activities	34
	10.1	Initiatives to support carbon footprint reduction goal	35
11.	Decl	aration and expectations	36

List of abbreviations

GHG – greenhouse gases
t CO2e – tonnes of carbon dioxi
tkm – tonne-kilometer
KOBIZE – the National Centre f
LB – location-based method
MB – market-based method
DEFRA – Department for Enviro
ADEME – Agence de la transitio

RES – renewable energy sources

kide equivalent

for Emissions Management

ronment, Food & Rural Affairs ion ecologique



Introduction

CARBON FOOTPRINT IS THE TOTAL SUM OF GREENHOUSE GAS EMISSIONS CAUSED DIRECTLY OR INDIRECTLY BY THE PRODUCTION OF A PRODUCT **OR PROVISION OF A SERVICE.**

Greenhouse gas emissions consist not only of emissions emitted by chimneys on factory premises, but also emissions associated with the production of utilities, raw materials or services purchased by companies, such as electricity, heat, main raw materials, auxiliary materials, semi-finished products or transportation services.

The greenhouse gases considered in the calculations are mainly carbon dioxide CO_2 , methane CH4 and nitrous oxide N_2O_2 . The report also specifies the carbon content of the product. In addition to the numerical results, the report also points out unique aspects to consider when evaluating the impact of paper packaging on carbon emissions and the environment as a whole.

This report is a summary of the performance of calculations of GHG (greenhouse gas) emissions.

The calculations and report were prepared in accordance with the following standards:

- The Greenhouse Gas Protocol A Corporate Accounting and Reporting Standard Revised Edition.
- GHG Protocol Scope 2 Guidance.
- Corporate Value Chain (Scope 3) Accounting and Reporting Standard.



Operational boundaries of the performed calculations

Scope 2 indirect energy GHG emissions	Scope 1 direct GHG emissions	
Consumption of purchased electricity and purchased heat.	Combustion of gasoline, diesel, LPG in the company's own fleet, consumption of light fuel oil and also use of industrial gases.	Cat. 1. Pu Cat. 3. En Cat. 4. Up Cat. 5. W Cat. 6. Bu Cat. 9. Do Cat. 12. D

Greenhouse gas emissions




THE ORGANIZATIONAL BOUNDARIES OF THE GHG EMISSION CALCULATIONS MADE INCLUDE THE ACTIVITIES OF DRUKPAK IN THE FULL RANGE OF PHYSICAL LOCATION AND ECONOMIC ACTIVITIES.

Carbon footprint analyses should identify a criterion for consolidating emission volumes at individual locations at the headquarters level.

> • operational control • financial control

The results were consolidated according to operational control at DrukPak, thus covering 100% of the gas emissions generated at the analyzed location.



Scope 2 Indirect (energy) emissions Emissions from heat or electricity generation

Scope 1 Direct emissions Emissions from fuel combustion at the production facility

7

6

Operational **boundaries**

The carbon footprint calculations included direct emissions, indirect emissions - energy, and other indirect emissions from the activities listed above.

> Scope 3 other indirect GHG emissions

- urchased raw materials.
- nergy and fuel-related emissions not included in Scope 1 and 2. Jpstream – transport and distribution.
- Vaste generated from operations.
- Business travel.
- Downstream transport and distribution.
- Dealing with sold products after use.

Scope 3 **Other indirect** emissions

Emissions related to the supply chain of goods and services





THE INPUT DATA FOR THE CALCULATIONS WERE SOURCED FROM THE COMPANY'S INTERNAL RECORDS.

A summary of the data sources used was detailed in a dedicated tool for collecting and calculating the carbon footprint.

In carrying out the carbon footprint calculation for 2022-2023, the same unit of consumption was used as in the calculations for previous years

4.] **Fuels**

Fuel consumption given in liters and tons was converted to consumption in GJ. The values in GJ were then multiplied by the corresponding emission indicators, yielding the result in t CO₂. In carrying out the carbon footprint calculation for 2022-2023, the same unit of consumption was used as in the calculations for previous years.

The Company generates thermal energy from its own boiler plants supplied with biogenic fuel (wood pellets).

The equipment also includes 3 EKOTERM fossil fuel (light fuel oil) boilers as a backup in case the pellet boilers fail. Heat consumption, given in GJ, was multiplied by the emission indicator, yielding the result in tCO₂. In carrying out the carbon footprint calculation for 2022-2023, the same unit of consumption was used as in the calculations for previous years.



Reporting period

Periods for which GHG emissions were calculated

January 1, 2022 to December 31, 2022



January 1, 2023 to December 31, 2023

4.2 **Process gases**

THE CALCULATION OF THE CARBON FOOTPRINT IN SCOPE 1 INCLUDES GHG EMISSIONS ASSOCIATED WITH PROCESS GASES USED IN THE PRODUCTION PHASE AND F-GASES USED IN REFRIGERATION EQUIPMENT

The gas quantities given were multiplied by the corresponding indicators obtained from conversions according to molar masses and volumetric CO₂ content (applies to gas mixtures with pure CO₂).



4.4

Cat. 1 **Purchased** raw materials and services

The analysis covered purchased raw materials and manufacturing services, as well as materials and services for office operations.

Consumptions of raw materials were multiplied by their dedicated indicators from DEFRA, Agri footprint 5., Ecoinvent 3.8., ADEME databases, and raw material emissivity documents obtained from manufacturers disclosing their carbon footprint on their websites.

For combined products formed from several elements, e.g.: plank+matrix+patrix, an average indicator was developed using individual indicators with the assumption of an equal share of individual raw materials in the material/object/mixed tool.

4.3 **Purchased electricity**

EMISSIONS RELATED TO ELECTRICITY CONSUMPTION WERE CALCULATED ACCORDING TO TWO METHODS: LOCATION-BASED AND MARKET-BASED.

2

Location-based method

is based on the country's average

Market-based method

involves converting electricity consumption multiplied by emission indicators published by specific energy sellers, which illustrates the impact of a company's purchasing decisions on the size of its carbon footprint

Electricity consumption, given in MWh or kWh, was multiplied by the average emission indicator for Poland and emission indicators published by energy sellers.

The energy purchased during the studied period was not covered by the RES guarantee of origin. If the purchased energy is covered by Guarantees of Origin, then the emission indicator is 0 tCO₂, regardless of the seller's published fuel mix.

The following assumptions were made for purchased services:





• maintenance services

- the number of tonkilometers traveled by the serviceman was calculated and multiplied by a dedicated indicator from the DEFRA database,

• laundry service

- the consumption of utilities required for the process was calculated using the Product Environmental Footprint Category Rules (PEFCR) Tshirts document. Normal washing at 40° and the following energy consumption were assumed: 0.510 MJ/kg; water consumption: 11.11 l/kg; wastewater: 11.11 l/kg,

10

IN TERMS OF 3 CATEGORY 1, EMISSIONS RELATED TO THE PRODUCTION OF GOODS AND SERVICES PURCHASED BY THE ORGANIZATION ARE INCLUDED.




• purchase of restorative meals - the calculated number of meals was multiplied by a dedicated indicator from the ADEME database.

4.5 Cat. 3. Energy and fuel-related emissions not included in Scope 1 and 2

Scope 3 in Cat 3 includes WTT (Well to Tank) emissions, i.e., emissions generated at the stage of fuel production and fuels for electricity generation and emissions related to the generation of electricity lost during transmission and distribution. They are part of WTW (Well to Wheel) emissions, or emissions from production to consumption of fuel/energy.

Example of WTW emissions for fuels



The remainder of the WTW emissions are Tank to Wheel (TTW) emissions, which arise from the combustion of fuels at facilities used by the entity (Scope 1) or from the production of electricity purchased by the organization (Scope 2).

Fuel and energy consumption data reported in Scopes 1 and 2 were used for the calculations, which were then multiplied by indicators from the DEFRA database



Cat. 4. Upstream – transport and distribution

CATEGORY 4 INCLUDES THE CARBON FOOTPRINT OF THE SUPPLY OF PURCHASED RAW MATERIALS AND EMISSIONS RESULTING FROM THE PERFORMANCE OF TRANSPORTATION AND DISTRIBUTION SERVICES PURCHASED BY THE ORGANIZATION, SUCH AS TRANSPORTATION OF FINISHED PRODUCTS, THE COST OF WHICH IS BORNE BY THE ORGANIZATION.

The analysis applies only to third-party transports (own fleet fuel consumption is shown in Scope 1).

Emissions are calculated based on the mass transported and the distance traveled by mode of transport, according to one of the rules:

- Providing a summary of transports, where each line corresponds to a single transport – distance traveled with cargo and the weight of that cargo.
- Providing aggregate data on transports, i.e., total weight transported during the reported period and average distance along the route.
- Providing aggregate data on transports, i.e., average weight transported per route and total distance traveled in the reported year.

Using one of the above three rules allows to correctly calculate the transport work performed (tonkilometers) and select an indicator appropriate to the tonnage and type of transport vehicle.

If you switch from road to sea or rail, or use any available mode of transportation, the calculation method is the same. The data acquired allowed the calculation of ton-kilometers traveled. The resulting ton-kilometers [tkm] were then multiplied by indicators from the DEFRA database.

4.7 Cat. 5. Waste generated from activities

The calculations include GHG emissions associated with the management of the resulting waste, subjected to various modes of transformation and management: recycling, disposal, landfilling or reuse.

The reported waste masses were grouped by type and management method; then the consumptions were multiplied by the corresponding emission indicators from the DEFRA database.



Included in Category 6 are business trips made by air, train, bus and non-business car (fuel consumption in business cars i s reported in Scope 1).

Calculations were made on the basis of statements showing the number of kilometers traveled by various means of transportation, obtaining data in the unit of passengerkilometer.

Dedicated emission indicators from the DEFRA database were used to calculate the carbon footprint of this category.

Cat. 9 Downstream transport and distribution

4.10 Cat. 12. **Dealing with** sold products after their end of life

Category 12. Applies to dealing with sold products after their end of life.

For the products sold, recycling was adopted as the recommended method of handling post-consumer waste.

The mass of products produced was converted by a dedicated indicator from the DEFRA database.



4.8 **Cat. 6 Business** travel

Category 9 takes into account transports of finished products carried out by external companies or customers, the cost of which is not covered by the reporting organization.

4.]] **Biogenic** emissions - outside the scopes

BIOGENIC MATERIALS, WHICH INCLUDE PELLETS, BIOMASS, BIOFUELS AND **BIOGAS, ARE INCREASINGLY BEING** USED IN ENERGY PRODUCTION.

At DrukPak, pellets are the main fuel for heat generation.

According to GHG Protocol, energy production using biogenic materials is much less carbon intensive compared to conventional feedstocks. This is due to a shortened (closed) carbon cycle the biomass consumed is generated in a natural cycle, and the CO₂ emissions themselves are of biogenic rather than fossil origin.

Therefore, CO₂ emissions from biomass combustion are calculated outside the scopes. The reported amount of pellets consumed was multiplied by the emission indicator derived from the DEFRA database.

GREENHOUSE GAS EMISSIONS REPORT 2022-2023

Emission indicators and conversion rates

THE FOLLOWING ARE SOURCES OF EMISSION INDICATORS WITH FULL NAMES AND LINKS (IF THE DATA IS PUBLICLY AVAILABLE).

For gasoline, diesel, LPG and light fuel oil, respective documents were used:

- Calorific values (WO) and CO emission indicators in 2021 for reporting under the Emissions Trading Scheme for 2023.
- Documents available at: https://www.kobize.pl/pl/ article/komunikaty/id/2523/wartosci- opalowewo-i-wskazniki-emisji-co2-we-w-roku- 2021-doraportowania-w-ramach-systemu-handluuprawnieniami-do-emisji-za-rok-2024r.
- The emission indicator for pure CO₂ equals the consumption value. Consumption in kilograms was converted to tons.
- The emission indicator for a mixture with CO2 (18%) - Ar 82% was calculated using a constant conversion rate according to molar masses and volumetric CO₂ content.
- The emission indicator for pellets and the biogenic emission indicator for pellets come from the DEFRA database (indicators to be updated annually).
- For waste, transports, WTT emissions and some raw materials, the DEFRA database was used. Indicators are available for waste in the "Waste disposal" sheet,

for transports in the "Freighting goods" sheet, for WTT emissions in the "WTT fuels" and "WTT-UK & overseas elec" sheets, for raw materials in the "Material use" sheet. DEFRA databases are available at: https:// www.gov.uk/government/ collections/governmentconversion-factors-for- company- reporting.

DRUKPAK | PRODUCT CARBON FOOTPRINT

- For some of the raw materials purchased, the Ecoinvent 3.8 database was used.
- For meals and shoes, the ADEME base was used. Available at the link: https://bilans-ges.ademe.fr/en/ accueil/authentification
- For other raw materials, documents from manufacturers and information from the following websites were used:
- www.afera.com/technical-centre/sustainability;
- https://www.klebstoffe.com/die-welt-des-klebens/ nachhaltigkeit-umwelt/product-carbon-footprint. html:
- https://ec.europa.eu/environment/eussd/smgp/ pdf/ PEFCR_tshirt.pdf
- The emission indicator for purchased heat is not applicable to DrukPak, due to in-house heat generation for the entire plant.
- The indicators for electricity from a particular seller (market-based method) come from the website of the energy seller in question.

The average emission indicator for electricity in Poland was calculated on the basis of data contained in the document "Emission indicators of CO₂, SO₂, NOx, CO and total dust for electricity on the basis of information contained in the National database on emissions of greenhouse gases and other substances for 2022".

Documents available at: https://www.kobize.pl/pl/article/aktualnosci-2022/id/2229/nowe-wskazniki-emisyjnoscidla-energii-elektrycznej.

The indicator has been converted to comply with the requirements of GHG Protocol.

The following conversions were made:

Emission indicators for electricity produced in Poland for 2022, published in December 2023 (used in calculations for 2022 and 2023).

144 443 114 MWh.

In the case of the analysis to determine the emission indicators for electricity at end-users, the balance of electricity, expressed in MWh, in 2022 was as follows:

• amount of electricity produced in combustion plants: 144 443 114

• amount of electricity produced from water 2 815 000

The balanced amount of electricity at end users was: 166 049 114 MWh

CO₂ emissions: 113 799 238 201 kg CO₂

(113 799 238 201 kg CO2) (144 443 114+2 815 000+27 602 000MWh)



For the location-based method, electricity consumption was multiplied by the average emission indicator for Poland. In contrast, the market-based calculation multiplied energy consumption by the emission indicator published by the energy seller.

17

16

The volume of electricity production reported from fuel combustion plants in reports to the National Base for 2022 amounted to

• amount of electricity produced from wind and other RES: 27 602 000

• balance sheet losses and differences: -8 811 000

685,33 kg CO₂/MWh

Results and commentary

CALCULATIONS WERE MADE FOR SCOPE 1, 2 AND 3 ACCORDING TO TWO METHODS: LOCATION-BASED (LB) AND MARKET-BASED (MB).

Biogenic emissions were also recorded as a result of pellet combustion at DrukPak, amounting to 414.26346 t CO₂e




Results of CO₂ emissions calculations for 2022-2023


7. **Carbon footprint – emissions by scope** with biogenic emissions

Emissions by scope


Line labels	Total from Emission volume 2023 [t CO_2e]	Total from Emission volume 2022 [t CO_2e]
Biogenic	414,26	613,67
Scope 1	1801,73	513,31
Scope 2	2322,78	2424,19
Scope 3	7556,30	10295,87









7.2 **Carbon footprint by emission category** – market-based method





Carbon footprint by emission category - market-based method 2023




7.3 **Carbon footprint** - location-based method

Electricity-related emissions calculated using Poland's average emission indicator

Line labels	Total from Emission volume 2023 [t CO2e]	Total from Emission volume 2022 [t CO2e]
Scope 1	1801,73	513,31
Scope 2	2509,63	2568,50
Scope 3	7556,30	10295,87
End total	11867,67	13377,68

Emissions by scope [t CO₂e]




Percentage share of scopes (location-based) in CO₂ emissions

Carbon footprint - location-based method

Electricity-related emissions calculated using energy sellerspecific emission indicator 2022

> Scope 1 Scope 2 Scope 3



Carbon footprint - location-based method


Electricity-related emissions calculated using energy sellerspecific emission indicator 2023

Scope 1
Scope 2
Scope 3



23






7.4 Carbon footprint – market-based method

Emissions by scope

Line labels	Total from Emission volume 2023 [t CO2e]	Total from Emission volume 2022 [t CO2e]
Scope 1	1801,73	513,31
Scope 2	2322,78	2424,19
Scope 3	7556,30	10295,87
End total	11680,81	13233,37

Electricity-related emissions calculated using energy seller-specific emission indicator




Percentage share of scopes (market-based) in CO₂ emissions

Carbon footprint - market-based method Electricity-related emissions calculated using energy sellerspecific emission indicator 2022 Scope 1 Scope 2 Scope 3


Carbon footprint – location-based method

Electricity-related emissions calculated using energy sellerspecific emission indicator **2023**

Scope 1
Scope 2
Scope 3



25





THE REPORT ON THE CARBON FOOTPRINT OF ALL PRODUCTS WAS COMPILED BASED ON THE LATEST AVAILABLE DATA FROM 2023.

Analyzing the size of carbon footprint of products on the basis of the latest data allows us to determine the carbon footprint of the solutions used and make changes that will minimize the company's overall environmental impact.

Product carbon footprint calculations were performed in accordance with the GHG Protocol Product Life Cycle Accounting and Reporting Standard.

Studies that only cover GHG emissions have the limitation of being able to ignore potential trade-offs and mutual benefits between different aspects of environmental impact. Therefore, the results of a study based only on GHG emissions calculations should not be used to communicate the overall environmental performance of a product.

7.5 **Biogenic** emissions - outside the scopes

Biogenic emissions at DrukPak arise from pellet combustion (fuel for CH and DHW) in the amount of 414.26346 t CO₂e in 2023 and 613.6684217 t CO₂e in 2022

The biomass consumed is generated in a natural cycle, and the CO₂ emissions themselves are of biogenic rather than fossil origin. Therefore, CO₂ emissions from biomass combustion are calculated outside the scopes.


Biogenic emissions - out of scope. **Reported out of** scope as additional information

volume 2023

414,26

Total from Emission volume 2022 [t CO₂e]

613,67



26

Product carbon footprint - overview

8.2 Unit of analysis and reference flow

1 kg of finished product was taken as the functional unit. The reference flow is 1 kg of final product, and the calculated emissions at each stage of the analyzed life cycle were related to it.

In addition to GHG emissions arising directly from the life cycle of the products studied, the analysis also included emissions arising from the electricity generation and industry used in the process, as well as the production of fuels (Well-To-Tank emissions).


In addition, GHG emissions accompanying the processing of waste generated by the Company's operations and the treatment of consumed tap water were calculated.


8.3 Zakres obliczeń dla produktów

The study was conducted on a cradle-to-gate basis - the calculated carbon footprint scopes from the extraction of raw materials to the creation of the finished product.

The following life cycle stages were included in the analysis:

- Extraction and pre-processing of raw material emissions generated during the extraction of raw material and its pre-processing.
- Transportation of raw material emissions generated during transportation of purchased raw material to the production facility.
- Production process direct emissions generated during processing and emissions related to the electricity used.





8.4 Allocation

ALLOCATION REFERS TO THE ATTRIBUTION OF GREENHOUSE GAS EMISSIONS GENERATED IN A UNIT PRODUCTION PROCESS TO THE PRODUCTS OF THE PROCESS.

It was conducted on a mass basis for each product. In the production phase, DrukPak consumes water, electricity and heat; plant waste is also generated as a result of the performed processes.

The number of tons of finished products was used to allocate consumptions to individual products, and the consumptions were presented in relation to 1 ton of finished product.

Consumptions for the production and administrative parts was allocated on an area basis, assuming that 92.12% of consumption comes from the production process while the remaining 7.88% is generated during administrative activities.

29

28

8.5 **Data and data** sources

The data used in the study came from the Company's internal electronic register "drupaczek", "radius" and from purchase invoices.

Emission indicators and conversion rates

The following are sources of emission indicators with names and links (if publicly available).

- For LPG, the KOBiZE document Heating Values (HV) and CO₂ Emission Indicators (EI) in 2021 was Scheme for 2024. https://www.kobize.pl/pl/ article/komunikaty/id/2523/wartosci-opalowewo-i-wskazniki-emisji- co2-we-w-roku-2021do-raportowania-w-ramach- systemu-handluuprawnieniami-do-emisji-za-rok- 2024r

Greenhouse gas reporting: conversion factors 2021

- Ecoinvent 3.8.
- https://www.afera.com/technical-centre/ sustainability/
- https://www.klebstoffe.com/die-welt-des-klebens/ nachhaltigkeit-umwelt/productcarbon-footprint. html



CARBON FOOTPRINT CALCULATIONS WERE PERFORMED FOR ALL PRODUCTS MANUFACTURED AT DRUKPAK, ON A CRADLE-TO-GATE BASIS.

 \frown

GREENHOUS

Results and commentary

database.

The second most emissive stage in the life cycle of the products analyzed is the production stage. Emissions from this stage range from 27.9% to 39.5% of total emissions. This is largely due to the reported volumes of utilities consumed. The emission indicator for electricity comes from information published by energy supplier PGE Obrót.

The stage of transporting raw materials to the factory accounts for the smallest share of total emissions is between 19.3% and 27% of total emissions. The input data used to calculate the emissions resulting from the transportation stage are estimates derived from the annual production volume at the factories and averaged data on the mode of transportation, its payload, the weight of the cargo transported and the distance.

The emission indicators used in the calculations are from the DEFRA (Department for Environment, Food & Rural Affairs) database and may differ from the actual emission indicators for transporting raw materials to the indicatory.



The largest share of the carbon footprint of the products analyzed is accounted for by emissions from the acquisition and pre-processing of raw materials. They range from 34.1% to 49.7% of total product lifecycle emissions. The differences are due to the type and quantity of raw materials used. Between 0.747 t CO₂e and 1.548 tCO₂e per ton of product is emitted into the atmosphere during the extraction and pre-processing stages. The emission indicators used are from the Ecoinvent

Carton

Flyer

The charts below show the carbon footprint of each product. There were no biogenic emissions in the analysis conducted.



2,000

1,500


1,000

0,500

0,000



Carton



Flyer

Label

9.] CART	ON IS THE PRIMARY PRODUCT MANUF	ACTURED AT DRUKPAK.			
	arbon footprint of one ton of finished pro	duct was 2,192 t CO₂e.			
Carbo	Carbon footprint of 1 ton of carton				
Life cycle stage	Carbon footprint of products [t CO2e/t]	Percentage of stages			
Raw materials	0,747	34,1%			
Emissions from transportation of raw materials	0,578	26,4%			
Produkcja, w tym:	0,867	39,5%			
Zużycie mediów	0,732	84,4%			
Materiały opakowaniowe	0,125	14,4%			
Odpady produkcyjne	0,011	1,21%			

9.	2	
F	lyer	

is shown in the table below.

```
Carbon footprint of 1 ton of leaflet
```

Life cycle stage	Carbon footprint of products [t CO2e/t]	Percentage of stages
Raw materials	0,940	49,7%
Emissions from transportation of raw materials	0,365	19,3%
Produkcja, w tym:	0,588	31,1%
Zużycie mediów	0,496	84,4%
Materiały opakowaniowe	0,085	14,4%
Odpady produkcyjne	0,007	1,2%

Label The p is sho	arbon footprint of one ton of finished pro ercentage of emissions arising in the sub wn in the table below. on footprint of 1 ton of label	
Life cycle stage	Carbon footprint of products [t CO ₂ e/t]	Percentage of stages
Raw materials	1,548	45,1%
Emissions from transportation of raw materials	s 0,927	27,0%
Produkcja, w tym:	0,958	27,9%
Zużycie mediów	0,808	84,4%
Materiały opakowaniowe	0,138	14,4%
Odpady produkcyjne	0,012	1,2%

33

32


The carbon footprint of one ton of finished product (leaflets) was 1,893 t CO₂e. The percentage of emissions arising in the subsequent stages of the life cycle

Reduction activities

ALL PAPER AND CARDBOARD PRODUCTS HAVE TWO UNIQUE POSITIVE CHARACTERISTICS:

- They are based on a renewable raw material wood. Wood binds CO2 during the growth phase.
- They store carbon, and by recycling paper and cardboard products, CO2 is retained and not released back into the atmosphere

Planned measures to reduce CO₂ emissions



sanitary facilities, etc., which will reduce energy consumption.

TIMING 2025-2027



Initiatives to support carbon footprint reduction goal

- Reduce the use of fossil fuels for thermal energy generation (CH and DHW) by using wood pellets in the company's boiler room.
- Reduce electricity consumption by replacing energy-intensive appliances with energy-efficient ones.
- Engage in dialogue with suppliers as part of efforts to reduce environmental footprint.
- Optimize transportation of finished goods and eliminate the so-called "empty kilometers" by planning the delivery of goods taking into account the location of deliveries, the size of cargo, the size of cargo spaces of cars, the possibility of using double deck trailers, i.e. 66 instead of 33 Euro pallets in a trailer, optimizing transport routes.
- Use DrukPak fleet cars with low emissions of substances harmful to human health and the environment, including carbon dioxide (CO₂), nitrogen oxide (NOx), sulfur oxide (SOx), hydrocarbon (HC), particulate matter (PM), carbon monoxide (CO), and other organic and inorganic compounds.
- Ensure high efficiency of CH and DHW infrastructure, ventilation, air conditioning and building infrastructure through regular inspections and maintenance.



Declaration and expectations

TO SUPPORT GLOBAL EFFORTS TO COMBAT CLIMATE CHANGE, DRUKPAK IS TAKING STEPS TO REDUCE ITS OWN GREENHOUSE GAS EMISSIONS AND ENCOURAGING ITS BUSINESS PARTNERS TO DO THE SAME.

We are implementing measures to reduce greenhouse gas emissions, aiming to achieve climate neutrality in terms of carbon footprint in 2030.

The actions taken are measurable and verifiable, so we have counted the CO₂e emissions resulting from our operations, which is evaluated and updated annually, along with determining further improvement actions.

We also present the above insights to our qualified suppliers, believing that a responsible supply chain is the key to effectively provide customers with quality products manufactured from the best quality materials, while supporting current and future generations, who should live in a sustainable world with environmental and social considerations. Through shared values, open communication and clearly established principles, we aim to ensure sustainable development.

We trust that the intended goals will be achieved by strengthening cooperation with our suppliers and customers, for whom sustainability issues are of equally high value.

What we expect from suppliers:

- Information on the product's carbon footprint, given in kg or Mg CO₂e per kg or Mg of product purchased, calculated in accordance with the GHG Protokol Product Standard or ISO 14067:2018.
- Product carbon footprint reduction plan.



) Oruk**Pak**

Stanisława Wyspiańskiego I Street 87-700 Aleksandrów Kujawski Poland Phone **+48 54 28 28 200** drukpak@drukpak.pl